




MMP BL86-425D-24V GRA81-124



DC MOTOR PERFORMANCE PARAMETERS:	VALUE	UNITS	TOLERANCE
Rated DC Voltage	24	DC VOLTS	-----
Rated Continuous Current	20.5	AMPERES	-----
No-Load Speed	5000	RPM	MAX
Rated Speed	3595	RPM	+/- 15%
Rated Continuous Power Out	330	WATTS	+/- 15%
Rated Continuous Torque	124	OZ-IN	-----
Peak Torque (motor only)	316	OZ-IN	-----
No-Load Current	1.39	AMPERES	MAX
Back EMF Constant (Ke)	4.8	V/KRPM	+/- 10%
Torque Constant (Kt)	6.5	OZ-IN/AMP	+/- 10%
DC Armature Resistance	0.33	OHMS	+/- 15%
Armature Inductance	0.27	mH	+/- 15%
Armature temperature	155	DEG. C	MAX

- ENCODER & BRAKE OPTIONS AVAILABLE – [FOLLOW THIS LINK FOR DETAILS](#)
- NEMA MOUNTING FLANGE OPTION AVAILABLE – [FOLLOW THIS LINK FOR DETAILS](#)

DESIGN, MANUFACTURING & DISTRIBUTION - MOTION CONTROL EQUIPMENT

email: sales@midwestmotion.com