




# REVERSIBLE BRUSHED DC MOTOR

**Model Number:**

**MMP S22-346G-36V**



DIMENSIONS ARE INCHES [MM] UNLESS OTHERWISE STATED

| DC MOTOR PERFORMANCE PARAMETERS: | VALUE | UNITS     | TOLERANCE |
|----------------------------------|-------|-----------|-----------|
| Rated DC Voltage                 | 36    | DC VOLTS  | ----      |
| Rated Continuous Current         | 7.9   | AMPERES   | ----      |
| No-Load Speed                    | 6000  | RPM       | MAX       |
| Rated Speed                      | 5126  | RPM       | +/- 15%   |
| Rated Continuous Power Out       | 209   | WATTS     | +/- 15%   |
| Rated Continuous Torque          | 55    | OZ-IN     | ----      |
| Peak Torque (motor only)         | 292   | OZ-IN     | ----      |
| No-Load Current                  | 1.05  | AMPERES   | MAX       |
| Back EMF Constant (Ke)           | 6.0   | V/KRPM    | +/- 10%   |
| Torque Constant (Kt)             | 8.1   | OZ-IN/AMP | +/- 10%   |
| DC Armature Resistance           | 0.67  | OHMS      | +/- 15%   |
| Armature Inductance              | 0.28  | mH        | +/- 15%   |
| Armature temperature             | 155   | DEG. C    | MAX       |

**NOTES:**

- ENCODER & BRAKE OPTIONS AVAILABLE – [FOLLOW THIS LINK FOR DETAILS](#)
- NEMA MOUNTING FLANGE OPTION AVAILABLE – [FOLLOW THIS LINK FOR DETAILS](#)

**MIDWEST MOTION PRODUCTS, INC**

**DESIGN, MANUFACTURING & DISTRIBUTION - MOTION CONTROL EQUIPMENT**

[www.midwestmotion.com](http://www.midwestmotion.com)

email: [sales@midwestmotion.com](mailto:sales@midwestmotion.com)