


**Model Number:****MMP D33-655D-36V GP81-308**

DIMENSIONS ARE INCHES [MM] UNLESS OTHERWISE STATED

| PLANETARY GEARMOTOR OUTPUT PARAMETERS:     | VALUE      | UNITS       | TOLERANCE |
|--------------------------------------------|------------|-------------|-----------|
| Gearhead Ratio (exact)                     | 307.54 : 1 |             |           |
| Gearhead Shaft Output Speed (at full-load) | 12         | RPM         | MAX       |
| Gearmotor Rated Continuous Torque          | 1951       | In-Lbs      | MAX       |
| Gearmotor Rated Peak Torque                | 2125++     | In-Lbs      | ----      |
| Gearhead Standard Backlash                 | 36         | Arc Minutes | MAX       |
| Gearhead Efficiency                        | 70%        | ----        | ----      |
| Output Shaft Radial Load Capacity          | 225        | Lbs         | MAX       |
| Output Shaft Axial Load Capacity           | 45         | Lbs         | MAX       |
| Gearmotor Total Weight                     | 15         | Lbs         | MAX       |

++ All Peak Torque values are dependent upon duty. Contact our sales office for details.

| DC MOTOR PERFORMANCE PARAMETERS: | VALUE | UNITS     | TOLERANCE |
|----------------------------------|-------|-----------|-----------|
| Rated DC Voltage                 | 36    | DC VOLTS  | ----      |
| Rated Continuous Current         | 13.1  | AMPERES   | ----      |
| No-Load Speed                    | 4091  | RPM       | MAX       |
| Rated Speed                      | 3657  | RPM       | +/- 15%   |
| Rated Continuous Power Out       | 391   | WATTS     | +/- 15%   |
| Rated Continuous Torque          | 145   | OZ-IN     | ----      |
| Peak Torque (motor only)         | 977   | OZ-IN     | ----      |
| No-Load Current                  | 0.91  | AMPERES   | MAX       |
| Back EMF Constant (Ke)           | 8.8   | V/KRPM    | +/- 10%   |
| Torque Constant (Kt)             | 11.9  | OZ-IN/AMP | +/- 10%   |
| DC Armature Resistance           | 0.29  | OHMS      | +/- 15%   |
| Armature Inductance              | 0.22  | mH        | +/- 15%   |
| Armature temperature             | 155   | DEG. C    | MAX       |

**NOTES:**

- ENCODER & BRAKE OPTIONS AVAILABLE – [FOLLOW THIS LINK FOR DETAILS](#)
- NEMA MOUNTING FLANGE OPTION AVAILABLE – [FOLLOW THIS LINK FOR DETAILS](#)

**MIDWEST MOTION PRODUCTS****DESIGN, MANUFACTURING & DISTRIBUTION - MOTION CONTROL EQUIPMENT**[www.midwestmotion.com](http://www.midwestmotion.com)email: [sales@midwestmotion.com](mailto:sales@midwestmotion.com)