BRUSHED DC GEARMOTOR

- **REVERSIBLE, PLANETARY GEARING**

Model Number:

MMP S40-775D-36V GP105-014



DIMENSIONS ARE INCHES [MM] UNLESS OTHERWISE STATED

PLANETARY GEARMOTOR OUTPUT PARAMETERS:	VALUE	UNITS	TOLERANCE
Gearhead Ratio (exact)	13.73 : 1		
Gearmotor Output Speed (at Cont. Torque)	241	RPM	+/- 15%
Gearmotor Rated Continuous Torque	161	In-Lbs	MAX
Gearmotor Peak Torque Capacity	1859++	In-Lbs	MAX
Gearhead Standard Backlash	36	Arc Minutes	MAX
Gearhead Efficiency	75%	-----	-----
Output Shaft Radial Load Capacity	203	Lbs	MAX
Output Shaft Axial Load Capacity	41	Lbs	MAX
Gearmotor Total Weight	14.5	Lbs	MAX

++ All Peak Torque values are dependent upon duty. Contact our sales office for details.

DC MOTOR PERFORMANCE PARAMETERS:	VALUE	UNITS	TOLERANCE
Input DC Voltage	36	DC VOLTS	-----
No-Load Current	2.48	AMPERES	MAX
No-Load Speed	3412	RPM	+/- 15%
Rated Continuous Torque	250	OZ-IN	MAX
Rated Continuous Current	20.2	AMPERES	MAX
Rated Speed (at Cont. Torque)	3310	RPM	+/- 15%
Rated Continuous Power Out	612	WATTS	+/- 15%
Peak Motor Torque	2888	OZ-IN	MAX
Peak Motor Current	207	AMPERES	MAX
Back EMF Constant (Ke)	10.5	V/KRPM	+/- 10%
Torque Constant (Kt)	14.1	OZ-IN/AMP	+/- 10%
DC Armature Resistance	0.07	OHMS	+/- 15%
Armature Inductance	0.12	mH	+/- 15%
Number of Motor Poles	4	(-)	-----
Armature temperature	155	DEG. C	MAX

NOTES:

1. Rated speeds may drop as the motor temperature increases. Values are stated with the motor at 25 °C.
2. All Peak Torque values are dependent upon duty. Contact our sales office for details.

ENCODER & BRAKE OPTIONS AVAILABLE – FOLLOW THIS LINK FOR DETAILS
NEMA MOUNTING FLANGE OPTION AVAILABLE – FOLLOW THIS LINK FOR DETAILS

MIDWEST MOTION PRODUCTS, INC
DESIGN, MANUFACTURING & DISTRIBUTION - MOTION CONTROL EQUIPMENT
www.midwestmotion.com email: sales@midwestmotion.com


GEARMOTOR CURRENT-TORQUE
MMP S40-775D-36V GP105-014
CURRENT (A)
250
200
150
100
50
0
0
500
1000
1500
2000
GEARMOTOR TORQUE (IN - LBS)
CONTINUOUS DUTY
INTERMITTENT DUTY


GEARMOTOR SPEED-TORQUE
MMP S40-775D-36V GP105-014
GEARMOTOR SPEED (RPM)
300
250
200
150
100
50
0
0
500
1000
1500
2000
GEARMOTOR TORQUE (IN-LBS)
CONTINUOUS DUTY
INTERMITTENT DUTY