


**Model Number:****MMP S27-411G-48V GP81-014**

DIMENSIONS ARE INCHES [MM] UNLESS OTHERWISE STATED

PLANETARY GEARMOTOR OUTPUT PARAMETERS:	VALUE	UNITS	TOLERANCE
Gearhead Ratio (exact)	13.73 : 1		
Gearhead Shaft Output Speed (at full-load)	304	RPM	MAX
Gearmotor Rated Continuous Torque	75	In-Lbs	MAX
Gearmotor Rated Peak Torque	483++	In-Lbs	----
Gearhead Standard Backlash	33	Arc Minutes	MAX
Gearhead Efficiency	75%	----	----
Output Shaft Radial Load Capacity	135	Lbs	MAX
Output Shaft Axial Load Capacity	27	Lbs	MAX
Gearmotor Total Weight	8.9	Lbs	MAX

++ All Peak Torque values are dependent upon duty. Contact our sales office for details.

DC MOTOR PERFORMANCE PARAMETERS:	VALUE	UNITS	TOLERANCE
Rated DC Voltage	48	DC VOLTS	----
Rated Continuous Current	9.96	AMPERES	----
No-Load Speed	4752	RPM	MAX
Rated Speed	4177	RPM	+/- 15%
Rated Continuous Power Out	359	WATTS	+/- 15%
Rated Continuous Torque	116	OZ-IN	----
Peak Torque (motor only)	750	OZ-IN	----
No-Load Current	1.46	AMPERES	MAX
Back EMF Constant (Ke)	10.1	V/KRPM	+/- 10%
Torque Constant (Kt)	13.7	OZ-IN/AMP	+/- 10%
DC Armature Resistance	0.58	OHMS	+/- 15%
Armature Inductance	0.47	mH	+/- 15%
Armature temperature	155	DEG. C	MAX

NOTES:

- ENCODER & BRAKE OPTIONS AVAILABLE – [FOLLOW THIS LINK FOR DETAILS](#)
- NEMA MOUNTING FLANGE OPTION AVAILABLE – [FOLLOW THIS LINK FOR DETAILS](#)

MIDWEST MOTION PRODUCTS**DESIGN, MANUFACTURING & DISTRIBUTION - MOTION CONTROL EQUIPMENT**www.midwestmotion.comemail: sales@midwestmotion.com