




BRUSHED DC GEARMOTOR
• REVERSIBLE, PLANETARY GEARING

Model Number:

MMP S40-775E-60V GP105-03.7



DIMENSIONS ARE INCHES [MM] UNLESS OTHERWISE STATED

PLANETARY GEARMOTOR OUTPUT PARAMETERS:	VALUE	UNITS	TOLERANCE
Gearhead Ratio (exact)	3.70 : 1		
Gearmotor Output Speed (at Cont. Torque)	1293	RPM	+/- 15%
Gearmotor Rated Continuous Torque	65	In-Lbs	MAX
Gearmotor Peak Torque Capacity	620++	In-Lbs	MAX
Gearhead Standard Backlash	33	Arc Minutes	MAX
Gearhead Efficiency	80%	-----	-----
Output Shaft Radial Load Capacity	135	Lbs	MAX
Output Shaft Axial Load Capacity	27	Lbs	MAX
Gearmotor Total Weight	14.5	Lbs	MAX

++ All Peak Torque values are dependent upon duty. Contact our sales office for details.

DC MOTOR PERFORMANCE PARAMETERS:	VALUE	UNITS	TOLERANCE
Input DC Voltage	60	DC VOLTS	-----
No-Load Current	2.12	AMPERES	MAX
No-Load Speed	4941	RPM	+/- 15%
Rated Continuous Torque	350	OZ-IN	MAX
Rated Continuous Current	23.3	AMPERES	MAX
Rated Speed (at Cont. Torque)	4783	RPM	+/- 15%
Rated Continuous Power Out	1238	WATTS	+/- 15%
Peak Motor Torque	3351	OZ-IN	MAX
Peak Motor Current	205	AMPERES	MAX
Back EMF Constant (Ke)	12.1	V/KRPM	+/- 10%
Torque Constant (Kt)	16.5	OZ-IN/AMP	+/- 10%
DC Armature Resistance	0.10	OHMS	+/- 15%
Armature Inductance	0.15	mH	+/- 15%
Number of Motor Poles	4	(-)	-----
Armature temperature	155	DEG. C	MAX

NOTES:

1. Rated speeds may drop as the motor temperature increases. Values are stated with the motor at 25 °C.
2. All Peak Torque values are dependent upon duty. Contact our sales office for details.

ENCODER & BRAKE OPTIONS AVAILABLE – [FOLLOW THIS LINK FOR DETAILS](#)

NEMA MOUNTING FLANGE OPTION AVAILABLE – [FOLLOW THIS LINK FOR DETAILS](#)

MIDWEST MOTION PRODUCTS, INC


DESIGN, MANUFACTURING & DISTRIBUTION - MOTION CONTROL EQUIPMENT

www.midwestmotion.com

email: sales@midwestmotion.com

GEARMOTOR CURRENT-TORQUE

MMP S40-775E-60V GP105-03.7



GEARMOTOR SPEED-TORQUE

MMP S40-775E-60V GP105-03.7

