


Model Number:
MMP D22-376H-60V GP52-130


DIMENSIONS ARE INCHES [MM] UNLESS OTHERWISE STATED

| PLANETARY GEARMOTOR OUTPUT PARAMETERS: | VALUE | UNITS | TOLERANCE |
|---|--------------|--------------|------------------|
| Gearhead Ratio (exact) | 129.62 : 1 | | |
| Gearhead Shaft Output Speed (at full-load) | 32 | RPM | MAX |
| Gearmotor Rated Continuous Torque | 199 | In-Lbs | MAX |
| Gearmotor Rated Peak Torque | 443++ | In-Lbs | ---- |
| Gearhead Standard Backlash | 48 | Arc Minutes | MAX |
| Gearhead Efficiency | 70% | ---- | ---- |
| Output Shaft Radial Load Capacity | 102 | Lbs | MAX |
| Output Shaft Axial Load Capacity | 34 | Lbs | MAX |
| Gearmotor Total Weight | 4.3 | Lbs | MAX |

++ All Peak Torque values are dependent upon duty. Contact our sales office for details.

| DC MOTOR PERFORMANCE PARAMETERS: | VALUE | UNITS | TOLERANCE |
|---|--------------|--------------|------------------|
| Rated DC Voltage | 60 | DC VOLTS | ---- |
| Rated Continuous Current | 2.64 | AMPERES | ---- |
| No-Load Speed | 5505 | RPM | MAX |
| Rated Speed | 4102 | RPM | +/- 15% |
| Rated Continuous Power Out | 106 | WATTS | +/- 15% |
| Rated Continuous Torque | 35 | OZ-IN | ---- |
| Peak Torque (motor only) | 102 | OZ-IN | ---- |
| No-Load Current | 0.28 | AMPERES | MAX |
| Back EMF Constant (Ke) | 10.9 | V/KRPM | +/- 10% |
| Torque Constant (Kt) | 14.8 | OZ-IN/AMP | +/- 10% |
| DC Armature Resistance | 5.79 | OHMS | +/- 15% |
| Armature Inductance | 5.07 | mH | +/- 15% |
| Armature temperature | 155 | DEG. C | MAX |

NOTES:

- ENCODER & BRAKE OPTIONS AVAILABLE – [FOLLOW THIS LINK FOR DETAILS](#)
- NEMA MOUNTING FLANGE OPTION AVAILABLE – [FOLLOW THIS LINK FOR DETAILS](#)

MIDWEST MOTION PRODUCTS

DESIGN, MANUFACTURING & DISTRIBUTION - MOTION CONTROL EQUIPMENT

www.midwestmotion.com

email: sales@midwestmotion.com