


**Model Number:****MMP D33-655H-90V GP81-079**

DIMENSIONS ARE INCHES [MM] UNLESS OTHERWISE STATED

PLANETARY GEARMOTOR OUTPUT PARAMETERS:	VALUE	UNITS	TOLERANCE
Gearhead Ratio (exact)	78.71 : 1		
Gearhead Shaft Output Speed (at full-load)	46	RPM	MAX
Gearmotor Rated Continuous Torque	517	In-Lbs	MAX
Gearmotor Rated Peak Torque	2125++	In-Lbs	----
Gearhead Standard Backlash	36	Arc Minutes	MAX
Gearhead Efficiency	70%	----	----
Output Shaft Radial Load Capacity	225	Lbs	MAX
Output Shaft Axial Load Capacity	45	Lbs	MAX
Gearmotor Total Weight	15	Lbs	MAX

++ All Peak Torque values are dependent upon duty. Contact our sales office for details.

DC MOTOR PERFORMANCE PARAMETERS:	VALUE	UNITS	TOLERANCE
Rated DC Voltage	90	DC VOLTS	----
Rated Continuous Current	5.32	AMPERES	----
No-Load Speed	4036	RPM	MAX
Rated Speed	3588	RPM	+/- 15%
Rated Continuous Power Out	397	WATTS	+/- 15%
Rated Continuous Torque	150	OZ-IN	----
Peak Torque (motor only)	963	OZ-IN	----
No-Load Current	0.36	AMPERES	MAX
Back EMF Constant (Ke)	22.3	V/KRPM	+/- 10%
Torque Constant (Kt)	30.2	OZ-IN/AMP	+/- 10%
DC Armature Resistance	1.88	OHMS	+/- 15%
Armature Inductance	1.34	mH	+/- 15%
Armature temperature	155	DEG. C	MAX

NOTES:

- ENCODER & BRAKE OPTIONS AVAILABLE – [FOLLOW THIS LINK FOR DETAILS](#)
- NEMA MOUNTING FLANGE OPTION AVAILABLE – [FOLLOW THIS LINK FOR DETAILS](#)

MIDWEST MOTION PRODUCTS**DESIGN, MANUFACTURING & DISTRIBUTION - MOTION CONTROL EQUIPMENT**www.midwestmotion.comemail: sales@midwestmotion.com