


Model Number:
MMP D22-301J-90V GP52-068


DIMENSIONS ARE INCHES [MM] UNLESS OTHERWISE STATED

PLANETARY GEARMOTOR OUTPUT PARAMETERS:	VALUE	UNITS	TOLERANCE
Gearhead Ratio (exact)	68.06 : 1		
Gearhead Shaft Output Speed (at full-load)	70	RPM	MAX
Gearmotor Rated Continuous Torque	54	In-Lbs	MAX
Gearmotor Rated Peak Torque	132++	In-Lbs	----
Gearhead Standard Backlash	48	Arc Minutes	MAX
Gearhead Efficiency	70%	----	----
Output Shaft Radial Load Capacity	102	Lbs	MAX
Output Shaft Axial Load Capacity	34	Lbs	MAX
Gearmotor Total Weight	3.6	Lbs	MAX

++ All Peak Torque values are dependent upon duty. Contact our sales office for details.

DC MOTOR PERFORMANCE PARAMETERS:	VALUE	UNITS	TOLERANCE
Rated DC Voltage	90	DC VOLTS	----
Rated Continuous Current	1.21	AMPERES	----
No-Load Speed	6977	RPM	MAX
Rated Speed	4760	RPM	+/- 15%
Rated Continuous Power Out	62	WATTS	+/- 15%
Rated Continuous Torque	18	OZ-IN	----
Peak Torque (motor only)	44	OZ-IN	----
No-Load Current	0.21	AMPERES	MAX
Back EMF Constant (Ke)	12.9	V/KRPM	+/- 10%
Torque Constant (Kt)	17.4	OZ-IN/AMP	+/- 10%
DC Armature Resistance	23.54	OHMS	+/- 15%
Armature Inductance	23.80	mH	+/- 15%
Armature temperature	155	DEG. C	MAX

NOTES:

- ENCODER & BRAKE OPTIONS AVAILABLE – [FOLLOW THIS LINK FOR DETAILS](#)
- NEMA MOUNTING FLANGE OPTION AVAILABLE – [FOLLOW THIS LINK FOR DETAILS](#)

MIDWEST MOTION PRODUCTS
DESIGN, MANUFACTURING & DISTRIBUTION - MOTION CONTROL EQUIPMENT
www.midwestmotion.com

 email: sales@midwestmotion.com