


Model Number:

MMP LA3-12V-40-A-250


DC LINEAR ACTUATOR

- **IP65 INGRESS PROTECTION**
- **BUILT-IN LIMIT SWITCHES AT EACH END OF TRAVEL**
- **ACME SCREW (ANTI-BACKDRIVING)**
- **NON-ROTATING ALUMINUM INNER TUBE**



Performance Parameters	Value	Units	Tolerance
Rated DC Voltage	12	VDC	----
Gear Ratio	40:1	----	----
Rated Force Capacity	225 (1000)	LBS (N)	MAX
Rated Current (at rated force capacity)	3.2	AMPERES	MAX
Rated Stroke Speed (at rated force capacity)	0.22 (5.6)	IN/SEC (MM/SEC)	± 10%
Stroke Speed at No-Load	0.28 (7.1)	IN/SEC (MM/SEC)	± 10%
Static Load Capacity	562 (2500)	LBS (N)	MAX
Maximum Recommended Duty	25%	----	MAX
Minimum Ambient Operating Temperature Range	-13 (-25)	°F (C)	MIN
Maximum Ambient Operating Temperature Range	149 (65)	°F (C)	MAX

PERFORMANCE CURVES:



• OPTIONAL MOUNTING BRACKET OPTION AVAILABLE – [FOLLOW THIS LINK FOR DETAILS](#)

MIDWEST MOTION PRODUCTS, INC.

DESIGN, MANUFACTURING & DISTRIBUTION - MOTION CONTROL EQUIPMENT

www.midwestmotion.com

email: sales@midwestmotion.com