




DC LINEAR ACTUATOR
• IP65 INGRESS PROTECTION
• BUILT-IN LIMIT SWITCHES AT EACH END OF TRAVEL
• ACME SCREW (ANTI-BACKDRIVING)


Model Number:

MMP LA5-12V-40-A-100



PERFORMANCE PARAMETERS	VALUE	UNITS	TOLERANCE
Rated DC Voltage	12	VDC	----
Gear Ratio	40:1	----	----
Rated Force Capacity	787 (3500)	LBS (N)	MAX
Rated Current (at rated force capacity)	11.0	AMPERES	MAX
Rated Stroke Speed (at rated force capacity)	0.29 (7.4)	IN/SEC (MM/SEC)	$\pm 10\%$
Stroke Speed at No-Load	0.33 (8.4)	IN/SEC (MM/SEC)	$\pm 10\%$
Static Load Capacity	1012 (4500)	LBS (N)	MAX
Maximum Recommended Duty	25%	----	MAX
Minimum Ambient Operating Temperature Range	-13 (-25)	$^{\circ}\text{F}$ (C)	MIN
Maximum Ambient Operating Temperature Range	149 (65)	$^{\circ}\text{F}$ (C)	MAX

PERFORMANCE CURVES:



• OPTIONAL MOUNTING BRACKET OPTION AVAILABLE – [FOLLOW THIS LINK FOR DETAILS](#)

MIDWEST MOTION PRODUCTS, INC

DESIGN, MANUFACTURING & DISTRIBUTION - MOTION CONTROL EQUIPMENT

www.midwestmotion.com

email: sales@midwestmotion.com